



# A POWERFUL PERFORMANCE EVERY TIME

Coupling power with incredible versatility, the FUSO FA is a masterpiece of form and function. Shifting value into high gear, the FA's durable, six-speed transmission and fuel-efficient common rail engine reduces operation costs so you can maximise profitability. Outstanding maneuverability strengthened by its incredible load capacity means there's no job too tough for this truck. The FUSO FA is built to deliver results.



**FA Rigid**

*\*Available in Single Cab and Chassis.*

---

Sales Representative



MITSUBISHI FUSO authorised distributor  
**ANSA MOTORS Chaguanas**  
[www.ansamotorstt.com](http://www.ansamotorstt.com)

## FA RIGID 4X2 SPECIFICATIONS

### MODEL

Model	FAV1PF1R - 17ft.	FAV1PH1R - 19ft.	FAV1PK1R - 21ft.
Crew	3 (1+2)		

### ENGINE

Model	4D37, 3.907-litre, 4-valve per Cyl.
Type	4-stroke cycle, water cooled direct injection, turbocharged diesel engine
Max. output	100kW/2,500rpm
Max. torque	420Nm/1,500rpm
Alternator	24V/45A

### DRIVE LINE

Clutch	Hydraulic control, diaphragm spring, single dry plate with concentric slave cylinder (CSC)
Transmission	Type 6-speed manual transmission
	Gear ratios 5.400-3.657-2.368-1.465-1.000-0.711-Rev: 5.400
Final reduction gear	Full floating type single reduction, hypoid
	ratio 5.13

### CHASSIS

Axle Capacity kg	Front	3,080	3,325	3,510
	Rear	6,520	6,275	6,090
Tire	Front	Single, 8.25-16-16PR		
	Rear	Dual, 8.25-16-16PR		
Suspension		Semi-elliptic, laminated leaf springs		
Brake	service	Full air, S-cam, dual circuit		
	parking	Spring actuated, pneumatically operated with hand brake valve		
	exhaust	Standard		
Fuel tank capacity		160L		
Electrical system-batteries		2x12V, 75Ah		

### DIMENSIONS mm (in.)

Wheelbase	(A)	3,760	4,250	4,800
Overall length	(B)	6,865	7,465	8,075
Overall width	(C)	2,215	2,215	2,215
Overall height, approx.	(D)	2,420	2,420	2,420
Axle Capacity kg	Front (E)	1,790	1,790	1,790
	Rear	1,690	1,690	1,690

### WEIGHTS kg

Kerb weight*	3,225	3,280	3,310
Max. G.V.W.	9,600	9,600	9,600

### CALCULATED PERFORMANCE

Max. Speed km/h	111
Max. gradeability (tan θ)%	27.8

\* Complete Cab chassis vehicle (without driver & rear body) with:

- Coolant
- Fuel tank filled with fuel of 90% of its capacity
- Spare wheel
- Standard tool kit
- Chocks
- All liquids to ensure correct functioning of vehicle
- Warning triangle (if provided)
- Jack & jack rod

### DRAWINGS (FAV1PH1R) (mm)

